

Water Solenoid Valve



| Overview |

This pilot operated diaphragm solenoid valve is suitable for liquid and gaseous fluid isolation (please check seal compatibility).

Ideal for use with the Flamefast GasGuard II to provide a complete services isolation system.

Technical Specification

Power Supply	230VAC
Power Consumption	< 0.1A
Max Pressure	15 Bar
Body Material	Brass
Internal Material	Brass & Stainless Steel
Media Temp	-10°C to 90°C
Connection	BSP
Seal	FPM
IP Rating	IP65
Approval	WRAS

Part Numbers & Options/Accessories

Part No	Description
WW15	1/2" Water Solenoid Valve (230V)
WW20	3/4" Water Solenoid Valve (230V)
WW25	1" Water Solenoid Valve (230V)
WW32	1 1/4" Water Solenoid Valve (230V)
WW40	1 1/2" Water Solenoid Valve (230V)
WW50	2" Water Solenoid Valve (230V)

Oil Solenoid Valve



| Overview |

This servo-operated general purpose solenoid valve is suitable for a wide range of media including Air, Water and Light Oils (up to 25 centistokes). Due to the assisted lift mechanism this valve can operate with a zero pressure differential.

When used with a Flamefast BoilerGuard this can be used to provide a complete and cost effective safety system for isolating fuel oil supplies to plant.

Technical Specification

Power Supply	230VAC
Power Consumption	< 0.1A
Max Pressure	15 Bar (up to 1") / 5 Bar (over 1")
Media Temp	-10°C to 80°C
Connection	BSP
Body Material	Brass
Internal Material	Brass & Stainless Steel
Seal	Nitrile
IP Rating	IP65

Part Numbers & Options/Accessories

Part No	Description
OV15	1/2" Oil Solenoid Valve (230V)
OV20	3/4" Oil Solenoid Valve (230V)
OV25	1" Oil Solenoid Valve (230V)
OV32	1 1/4" Oil Solenoid Valve (230V)
OV40	1 1/2" Oil Solenoid Valve (230V)
OV50	2" Oil Solenoid Valve (230V)